

KNITTOL XL

SEMI SYNTHETIC KNITTING OIL FOR NEEDLES AND SINKERS ON CIRCULAR KNITTING MACHINES

KNITTOL XL is a high performance lubricant based on especially refined lubricating oils blended with synthetic lubricants.

KNITTOL XL contains extreme pressure and anti-wear additives which guarantees low wear even at highest speed of the machines

KNITTOL XL has excellent oxidation stability. It does not thicken or form resinous deposits on loop forming elements on the machines.

KNITTOL XL contains emulsifiers, a high viscosity index and the viscosity group 22 allows an easy starting of the machines at low temperatures and also safe lubrication even under hot running conditions.

KNITTOL XL may be used with any normal methods including automatic lubrications.

KNITTOL XL has an excellent consistent with plastics and paintings.

KNITTOL XL is an universal product for modern knitting mills with high speed circular knitting machines with fine guage and a high number of systems.

Appearance	:	Colourless oil	
Viscosity 40°C	:	21,6 mm ² /s	DIN 51 562
Viscosity Group	:	22 ISO/VG	DIN 51 519
Viscosity Index	:	+95	ISO 2 908
Density 15° C	:	0,862 g/ccm	DIN 51 757
Flash Point C O C	:	175 ° C	