

SELCO PIPE SEALANT WITH TEFLON

DESCRIPTION

SELCO Sealant is a superior lubricating and anti-seize sealant formulated to provide maximum thread lubrication in a wide range of pipe threads and fittings. The use of Teflon® and other solid lubricant additives in Selco Sealant allows greater thread engagement which enhances sealing. Selco Pipe Sealant prevents corrosion and galling of threads for easy disassembly. Recommending for use on black iron galvanized, stainless steel, and high pressure steam pipes in contact with cast iron, maleable, brass, stainless steel and galvanized fittings.

BENEFITS

Prevents corrosion, galling and seizing, Assures easy disassembly, Suitable for water, natural gas, air, steam and hydraulic as well for all combinations of pipe and fittings, Non-toxic and non-hazardous

APPLICATIONS

Water lines, non-potable, Steam pipe fittings. Hydraulic lines and fittings, Pneumatic systems
Natural gas lines.

TECHNICAL SPECIFICATIONS

Colour	Off white	
Temperature Range	10° F to 350° F	
Water Resistance	Excellent	
Particle Size	2 ml. maximum	
Viscosity (cps) @ 250° C	400,000	
Specific Gravity	1.15	
Coefficient of Friction "K" Factor	0.16	
		<u>ASTM Test Method</u>
Flash Point	260° C (500° F)	D-92
Dropping Point	388° F	D-566
Copper Corrosion test (212° F, 24 hours)	No corrosion	D-130-83